



Manufacturers of Commercial and Residential Quality Carpet Cushion

EFFECTIVE DATE - 1/5/05

TITANIUM LAMINATE CUSHION
(For Laminate Floors)

COLOR	GREEN
WEIGHT (OZ./SQ.YD.)	44
THICKNESS	2.5 mm/.10"
DENSITY (LBS./CU.FT.)	37
DESIGN CONFIGURATION	F/F
BACKING/TOP	POLYESTER NON-WOVEN
BACKING/BOTTOM	SILVER MOISTURE PROOF (SEAMS MUST BE TAPED)
WIDTH INCHES	54
LENGTH/ROLL, FEET	48
SQUARE YARDS/ROLL	24 (216 Sq. Ft.)
APPROX. SHIPPING WGT. (LBS. PER ROLL)	70
ANTI MICROBIAL	YES/GUARDIAN
MOLD/MILDEW RESISTANT	NO GROWTH
PILL TEST DOC-FF 1-70: (ASTM-2859)	PASSES
R-VALUE	.097

IMPACT INSULATION CLASS IIC-58 w/laminate

SOUND TRANSMISSION CLASS STC-52 w/laminate

REFLECTIVE SOUND REDUCTION: Tested 4.0 dBA to 7.0 dBA quieter than standard foam paddings when tested as an assembly with laminate flooring. Measurements taken between 2000 Hz and 4000 Hz utilizing, the tapping machine described in ASTM-E492 as an impact noise generator.